SENSORFLOW 21

A4848AA

SILVER ecovadis

SENSORFLOW 21 | Wall-mounted basin tap 50x196x50 mm, 230 mm spout projection in chrome finish, 3.7 l/min (3 bar), no waste | Panel installation, Touchless control, Vandalresistant, SmartShine


Image & drawing





General information	
Product type:	Washbasin mixers
Sub product type:	Wall-mounted basin tap
Brand:	Armitage Shanks
Suite name:	SENSORFLOW 21
Designer:	Artefakt
Colour:	AA - Chrome
Surface finish effect:	glossy
Height (mm):	50
Width (mm):	50
Length / Projection (mm):	196
Net weight (kg):	1.98
EAN code:	4015413323390

Designed to be supplied with pre-mixed water. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device, please see A5900AA (for use with 15mm pipework) or A5901AA (for use with 22mm pipework). The downward pointing sensor is set to work in the normal handwashing position. This helps to eliminate false triggering from high visibility clothing associated with forward facing sensors, we also do not recommend the use of chromium plated wastes. Automatically shuts off if sensor is obstructed for a maximum of 55 seconds. Stand alone battery powered unit. Flow rate regulated to 3.7 litres per minute at 1 bar.



Features



• Installation Guide

• Spare Parts List

Product standard & certifications

Additional standards:	EN 248 DIN 4109-1 EN 15091
WRAS certificate name:	1710043

Product specifications

Amount of escutcheon(s):	1
Amount of handles:	0
Blue Start technology:	No
Colour code:	AA
Colour description:	chrome
Cool Body technology:	No
Easy Fix technology:	No
Includes a chain eye:	No
Integrated electronics:	Yes

SENSORFLOW 21

SENSORFLOW 21 | Wall-mounted basin tap 50x196x50 mm, 230 mm spout projection in chrome finish, 3.7 l/min (3 bar), no waste | Panel installation, Touchless control, Vandal-resistant, SmartShine

Product specifications

Low-pressure model:	No
Material:	Metal
Material quality:	Brass
Max. flow rate at 3 bar (l):	3.7
Max. flow rate at 3 bar (l) for all outlets:	3.7
Max. flow rate at 3 bar (l) for spout:	3.7
Max. operating pressure (bar):	5
Min. operating pressure (bar):	0.1
Operating method:	Contactless
PVD technology:	No
Shape of escutcheon(s):	Round
SmartShine:	Yes
Spout model:	Fixed
Surface cover:	chromium-plated
Surface finish effect:	glossy
Tap outlet model:	Aerator
Tap outlet visibility:	Visible
Tap outlet adjustable:	No
Tap outlet is anti-vandal:	Yes
Touchless control:	Yes
With drain plug:	No
With escutcheon(s):	Yes
With handle(s):	No
With outlet:	Yes
With pull-out spray:	No
With waste set:	No
Mounting method:	Panel mounted



A4848AA





Your local contact:

België • Belgique

Ideal Standard Produktions GmbH Ikaroslaan 18 B-1930 Zaventem ① +32 2 325 66 00 ⊒ +32 2 325 66 01 www.idealstandard.be

България

Идеал Стандарт - Видима АД ул. "Марин Попов" 53 гр. Севлиево, 5400 Ф +359 885 938 880 office@idealstandard.com www.idealstandard.bg

Česká republika

Hrvatska

Ideal Standard Hrvatska Lopatinečka ul. 8 10000, Zagreb ① +385 91 229 9304 www.idealstandard.hr

Danmark

Ideal Standard Skandinavia ApS Fynsvej 9 5500 Middelfart (Denmark) ① +45 75 84 10 10 www.idealstandard.dk

Deutschland

Ideal Standard GmbH Euskirchener Straße 80 53121 Bonn ① +49 (0)228 521-0 ⊒ +49 (0)228 521-241 ⊠ idealstandard.de@idealstandard.com www.idealstandard.de

Éire

Ideal Standard Éire 2nd Floor, Unit 3103 Lake Drive Citywest Business Campus Tallaght Dublin 24 YXW2 (1) +353 1 4564525 www.idealstandard.ie

España

Ideal Standard Iberia S.L.U Riera Principal Nr. 8 08328 Alella (Barcelona - España) (1) +34 93 561 80 00 www.idealstandard.es

Ελλάδα

Ideal Standard S. Α. Γραφεία Αθηνών: Λ. Μεσογείων 265, 15451 Ν. Ψυχικό, Αθήνα Φ +2106790800 www.idealstandard.gr

France

Ideal Standard France - Siège social 39Rue St. Sabin 75011 Paris (2) +33 (0)1 49 38 81 34

- 0 +35 (0)1 49 58 81 54
- sav.idealstandard@idealstandard.com
 (demandes techniques) /
 devis.chantier@idealstandard.com
 (demandes commerciales)
 www.idealstandard.fr

Italia

Ideal Standard (Italia) Srl Via Giosuè Borsi 9 20143 Milano, Italia → +39 (0)2 28881
 info@idealstandard.it
 www.idealstandard.it

Nederland

Österreich

Ideal Standard GmbH Zweigniederlassung Österreich Erzherzog-Karl-Str. 131–135 1220 Wien Österreich ③ +43 125 66 222-0 ⊒ +43 125 66 222-625 www.idealstandard.at

Polska

Ideal Standard Polska UI, Ostrowskiego 7 53-238 Wroclaw ① +48 71 78 68 301 www.idealstandard.po

România

Srbija

Ideal Standard - Vidima AD Drinčićeva br.19, I sprat, stan br.8 11000 Beograd Srbija © +381 11 7138 058 www.idealstandard.rs

United Kingdom