



This exploded view diagram illustrates the components of a kitchen sink faucet assembly, numbered 1 through 12:

- 1**: Faucet handle.
- 2**: Decorative cap and O-ring for the handle base.
- 3**: Cartridge assembly with a side lever.
- 4**: O-ring for the cartridge.
- 5**: Mounting bracket and screws for the faucet body.
- 6**: Faucet body.
- 7**: Mounting hole in the sink deck.
- 8**: Mounting nut and washer.
- 9**: Mounting plate for the drain.
- 10**: Drain assembly with a long tailpiece.
- 11**: Drain assembly with a shorter tailpiece.
- 12**: Drain cap.



0721 / A 866 025
Made in Germany

The technical drawings show two faucet models, A and B, with their respective dimensions:

- Faucet Model A (Left):**
 - Total height: 149 mm.
 - Spout height from mounting surface: 78 mm.
 - Spout angle: 13°.
 - Mounting hole diameter: Ø51 mm.
 - Base plate diameter: Ø35 mm.
 - Maximum base plate thickness: max. 35 mm.
 - Maximum cartridge length: max. 150 mm.
 - Cartridge diameter: Ø63 mm.
 - Cartridge height: 30 ± 50 mm.
 - Connection type: G1 1/4.
 - Bottom connection diameter: Ø15 mm.
- Faucet Model B (Right):**
 - Total height: 149 mm.
 - Spout height from mounting surface: 78 mm.
 - Spout angle: 13°.
 - Mounting hole diameter: Ø51 mm.
 - Base plate diameter: Ø35 mm.
 - Maximum base plate thickness: max. 35 mm.
 - Bottom connection diameter: Ø15 mm.

A 5535 ..



www.idealstandardinternational.com



